

Product Data Sheet  
Edition 09.2014  
Identification No. N - 6



## SURFAPORE F

Water Based, Primer For Fibrous Materials & Wood For Protection Against Water & Oil

### Description

It is water based, nano primer for the protection of fibrous materials as carton, Kraft paper, plaster boards, dry walls, composite wood and gypsum plaster against oil, water, moisture, mould and micro organisms. It also improves paint adhesion.

It complies with Rilem test 11.4.

### Where to use

- Y a e n i a e a a u a a i i c e & t i [ ] A a a a [ ! ] t i c a A , a i [ ^ . A ^ i a e a .
- Y a e n i i [ [ . A i ^ , a p i A i a e c i A i a e a .
- O a e A a A . a a a e a a i a a i .

### Advantages

- S i } \* A e e t i } \* .
- O e ^ A ^ i a e a a e i [ ] .
- U i [ { [ c . A a e a e a @ . a } .
- Y a e n i a e a a .
- O c d ^ { a r A [ , A U O .
- O [ . o f f e & t i v e .
- A i [ c e & a e i { } [ [ . a a [ [ [ a a e a a e a d } [ i A \ i a e a a e a i .
- U i a c a ^ c a A [ ^ i a A i [ , c @
- U i a c a ^ c a A a e a a \* .
- U i a c a ^ c a A , a i i a \* .

### Properties

Form	Milky water emulsion
Density	1.01gm/cm <sup>3</sup>
Viscosity	4 Mpa.s
Color	White
Water absorption reduction	93%

### How to Use

#### Surface preparation:

- The application surface should be dry and clean.

#### Application:

- Apply SurfaPore F by using a brush or roller.

- No dilution is required.
- On very absorptive surfaces reapply within 3 hours.
- Maximum protection efficiency is achieved 24 hours post application.

#### Theoretical Coverage:

Estimated consumption rate 8-10 m<sup>2</sup>/L, strongly dependant on the absorptivity of the surface applied.

#### Packaging:

1L, 4L, 10L, 30L Containers, 1000L IBCs

#### Shelf Life & Storage:

**SURFAPORE F** has a shelf life of 18 months at least when stored in normal dry condition.

### Health and Safety

- Care should be taken to avoid inhalation of dust and to prevent material entering the eyes.
- Use goggles-gloves and a breathing mask when applying.
- Apply forced ventilation in confined spaces.
- Remove splashes from skin with hand cleanser or soap and water.
- Eye splashes to be washed with plenty of water.

### Additional Information

**PROKEM** provides the construction industry with a comprehensive range of construction Chemicals and specialty products answering the queries of modern engineers for trouble free durable structure.

**PROKEM** designs tailor made products should there be critical application that requires specific properties rather than our main range. For our customer's satisfaction, **PROKEM** extends technical services to include after sales support to assist users in a proper handling of our products.